

Ask about
Singlas Calibration

Applications

Food Service, Delivery & Preparation,
HVAC, Refrigeration & Airconditioning,
Equipment Monitoring, Laboratories &
Cleanroom, HACCP Programs



Big Display Thermo-Hygrometer

SPECIFICATIONS

Big & easy to read display :	(80mm x 62mm)
2-key operation :	Max/Min and Reset
Measuring range :	Temperature -10 C to +60 C
Accuracy :	Temperature +/- 1 C
Measuring range :	Humidity 10% to 99% R.H
Accuracy :	Humidity +/-5% R.H
Unit size :	L110 x W100 x D20.4mm
Features for hanging & standing purposes C/ F selectable switch	
Low-battery warning	
Battery enclosed	
Memory for highest and lowest temp. & humidity	

MODEL	DESCRIPTION
AZ-HT-02	Big Display Thermo-Hygrometer
CAL	Traceable Calibration Certificate with Data

Digital Thermo-Hygrometer with external probe

Applications

Food Service, Delivery & Preparation,
HVAC, Refrigeration & Airconditioning,
Oven & Chamber Testing with probe,
Laboratories & Cleanroom, HACCP
Programs



SPECIFICATIONS

Measuring temperature	-50 ~ 70°C
External Probe Length	9.5 ft
Temperature Resolution	0.1°C
Temperature Accuracy	0 ~ 40°C: ±1°C 40 ~ 50°C and -40 ~ 0°C: ±2°C -50 ~ -40°C and 50 ~ 70°C: ±2.5°C
Measuring Humidity	20% ~ 95% RH
Humidity Accuracy	±5% RH for 40% ~ 70%RH ±10% RH for 20%~39%RH, 71%~90%RH +15% RH for 91% ~ 95%RH
Humidity Resolution	1%RH
Power Source	1pc AAA (1.5V) Battery
Unit Size	108 x 85 x 15mm

MODEL	DESCRIPTION
BG-HT-03	Digital Thermo-Hygrometer with external Temperature Probe
CAL	Traceable Calibration Certificate with Data